H

Heckmann Building Products Inc.

1501 N. 31st Avenue Melrose Park, IL 60160-2911 800-621-4140 or 708-865-2403 Fax: 708-865-2640

www.heckmannbuildingprods.com

SUBMITTAL SHEET: 600 SERIES JOIST AND BEAM ANCHORS

Used for attaching wood joists to Structural Steel Beams. The Flange hook is $\frac{3}{4}$ " deep with a 1-1/4" return. Manufactured in 1/8" thick x 1-1/4" Mill Galvanized Steel in the following styles:

NO. 600 ARM-UP JOIST AND BEAM ANCHOR: Anchors joist to the top of the beam. Standard Size is a 4" long flange with a 10" arm – Mill Galvanized Steel. Custom Sizes Available.

No. 601 ARM-DOWN JOIST AND BEAM ANCHOR: Anchors Joist below the top flange of the beam. Two standard sizes:

6-1/2" across the flange with a 10" Arm Mill Galvanized Steel.

8-1/2" across the flange with a 12" Arm Mill Galvanized Steel.

Custom Sizes Available.


No. 604 DOUBLE-ARM JOIST AND BEAM


ANCHOR: Anchors Joists framing into each side of the beam. Two standard sizes:

6-1/2" across the flange with a 10" Arms Mill Galvanized Steel.

8-1/2" across the flange with a 12" Arms Mill Galvanized Steel.

Custom Sizes Available.





Stainless Steel:

Sheet metal anchors and ties: ASTM A 167 AISI Type 304

Plate and bent bar anchors: ASTM A 666 AISI Type 304. Wire ties and anchors: ASTM A 580 AISI Type 304.

Hotdip Galvanized:

ASTM A 153 Class B-2: (1.50 oz/ ft².)(0.46kg/m²)

Mill Galvanized:

Sheet metal anchors and ties: ASTM A 653 G60

Wire: ASTM A 641 (0.1 oz/ ft^2 .)

Plain Steel:

Sheet Metal anchors and ties: ASTM A 569, ASTM A 366. Plates, bars, and shapes: ASTM A 123, ASTM A 36.

Wire: ASTM A 82, ASTM A 82-95a.

Approvals:
Comments: