



Heckmann Building Products Inc.

1501 N. 31st Avenue

Melrose Park, IL 60160-2911

800-621-4140 or 708-865-2403 Fax: 708-865-2640

www.heckmannanchors.com

SUBMITTAL SHEET:

No. 78 PINTLE STONE ANCHORS

Custom Made:

For use with the Original Pos-I-Tie® Barrel Screw and the ThermalClip®.

1/8" x 2" wide only. Stainless Steel.

Pintle stone anchors are notched to fit in the ThermalClip® with the Original Pos-I-Tie® system. Specify Length from bend in pintle to od of anchor.

78-S Split-Bend Pintle Stone Anchor – Specify split-bend lengths (od).

78-Z Z-Type Pintle Stone Anchor - Specify bend length (od)

78-U U-Type Pintle Stone Anchor – Specify bend length (od)

78-P – Pin-Type Pintle Stone Anchor – Specify diameter and length of pin, hole location, pin loose, fixed or welded.



78-S



78-Z



78-U



78-P



1/8" x 2" wide with 1" splitbends
Vertical adjustment 1"
Ultimate Design Loads compression
and tension

1/4" extension	160 lbs
1/2" extension	64 lbs
3/4" extension	40 lbs
1" extension	28 lbs

Installation of the Pos-I-Tie® screw should be within 1/4" below joint to achieve the best load.

Stainless Steel:

Sheet metal anchors and ties: ASTM A 167 AISI Type 304.

Plate and bent bar anchors: ASTM A 666 AISI Type 304.

Wire ties and anchors: ASTM A 580 AISI Type 304.

Type 316 Stainless Available upon request.

Approvals:

Comments: