

1007 Drip-Edge Flashing

SECTION 04 00 00 MASONRY Section 04 05 23 Masonry Accessories Section 07 62 00 Sheet Metal Flashing and Trim

PART 1: GENERAL

1.1 RELATED SECTIONS

- A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

- A. Manufacturer Certificate of Compliance for materials.
- B. Product Data: Manufacturer's data sheet on each type of product furnished.

PART 2: MANUFACTURER

2.1 MANUFACTURER

Acceptable Manufacturer:
Heckmann Building Products
110 Richards Ave.
Norwalk, CT 06854-1685
800-621-4140
Email: info@heckmannanchors.com
Website: www.heckmannanchors.com

2.2 APPLICATIONS

- A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-22.
- B. Stainless Steel AISI [Type 304] [or] [Type 316]
- C. ASTM A240/A240M-15b Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Application.
- D. ASTM A666-15 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.

2.3 MATERIALS

NO. 1007 DRIP-EDGE FLASHING

Standard: 26 gage x 3" wide with 1/2" drip hemmed back 3/8" x 8 ft long

Custom: 26 gauge x [width] with 1/2" drip hemmed back 3/8" x 10 ft long

A. Materials: [Type 304 Stainless Steel]

PART 3: EXECUTION

A. Install as specified in applicable Masonry/Sheet Metal Flashing section(s).