


Submittal Sheet
#134 Channel Slot Corrugated Anchor

Used to attach brick veneer to backup with Channel Slots. (See #130, #131, #132, or #133 Channel Slots)

Also Available in #710 Zinc Alloy in 1/8" thick and 16 gage for use as a firewall melt-away anchor



Standards:

Thickness: 16 gage

Width: 1-1/4"

Length from face of channel: 3 1/2" 5 1/2" 7 1/2" other

Specials:

Thickness: 1/8" 12 gage 14 gage 16 gage

Length (minimum 1-1/2"): _____

Width: 1-1/4"

Finish: Stainless type 304 Hot Dip Galvanized
 Mill Galvanized Zinc Alloy 710
 (1/8 & 16 ga only)

Quantity: _____

Material Specifications

Stainless Steel: Sheet metal anchors and ties: ASTM A 167, ASTM A 666, ASTM A 240/A240M AISI Type 304.

(AISI Type 316 available upon request)

Hotdip Galvanized: ASTM A 153 Class B-2: (1.50 oz/ ft²)(0.46kg/m²)

Mill Galvanized: Sheet metal anchors and ties: ASTM A 653 G60

Plain Carbon Steel: ASTM A1008/A1008M Structural Steel ASTM A36/A36M-08

Firewall Anchors: Rolled Strip Zinc Alloy 710. (Firewall alloy 1/8" and 16 gage only)