HECKMAN Building Produc	N ets Submittal Sheet #196 Corrugated-Type Column Anchor
Length	Notch depth Length end to notch start Notch opening
QUANTITY:	
THICKNESS: 3/16" 1/8"	MATERIAL TYPE:Type 304 Stainless SteelType 316 Stainless SteelZinc Alloy 710 (1/8" Only)
Stainless Plate Min. Fy. = 45,000 psi (ASTM A666)	Plain Carbon Steel*  *Plain Carbon Steel for end user plating - not reccommended for direct installation  CLICK OR SCAN FOR MATERIAL SPECIFICATIONS
PROJECT DETAILS:	CONTACT INFO
LOCATION:	NAME:
PROJECT NAME:	COMPANY:
NOTES:	PHONE:
	E-MAIL:
Heckmann is not responsible for your choice of anchors and dimensions for your project. The choice of anchors and products should be decided by the architects or engineers knowledgeable with the project.	DATE:
Once a custom order has been placed it cannot be cancelled or returned. Any changes to the original order may require additional charges. Your signature is required for us to proceed. By signing this order, you agree that you have reviewed the details and specifications of the custom order and that said details and specifications are per your request. Further, by signing this order you are waiving <b>any claim</b> against or right of non-payment for products produced to the specifications of the order.	ACCEPTED BY:

## www.heckmannanchors.com info@heckmannanchors.com