

#282-N Pintle Wire Tie for Pos-I-Tie® ThermalClip®

SECTION 04 00 00 MASONRY
Section 04 05 19.16 Masonry Anchors
Section 04 05 23 Masonry Accessories

PART 1: GENERAL

1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

PART 2: MANUFACTURER

2.1 MANUFACTURER

Heckmann Building Products
110 Richards Ave.
Norwalk, CT 06854-1685
800-621-4140
Email: info@heckmannanchors.com
Website: www.heckmannanchors.com

2.2 APPLICATIONS

- A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-22.
- B. ASTM A1008/A1008M Sheet Metal Anchors and Ties (Plain Steel).
- C. ASTM A153/A153M-16 Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware.
- D. Stainless Steel AISI Type 304
- E. ASTM A240/A240M-15b Standard Specification for Chromium and Chromium Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Application.

F.ASTM A666-15 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.

2.3 MATERIALS

Select the following

No. 282-N PINTLE WIRE TIE FOR THERMALCLIP®: 3/16" dia. [3"] [3.5"]
[4"] [5"]

Insert into Pos-I-Tie® ThermalClip® and adjust vertically to fit brick veneer mortar joint:

Materials: [Hotdip Galvanized After Fabrication] [Type 304 Stainless Steel]

PART 3: EXECUTION

A. Install as specified in applicable masonry section(s).