

### **340 Series Anchors**

- #340 Corrugated L-Anchor
- #340-A Corrugated L-Anchor with Hole
- #340-B Corrugated L-Anchor with Slot
- 341 L-Anchor with Hole
- #341-A L-Anchor with Hole
- #341-B L-Anchor with Two Holes
- #342 L-Anchor with Slot
- #342-A L-Anchor with Hole and Slot
- #342-B L-Anchor with Two Slots

SECTION 04 00 00 MASONRY  
Section 04 05 19.16 Masonry Anchors

## **PART 1: GENERAL**

### 1.1 RELATED SECTIONS

- A. Provide shop drawings for all product locations.

### 1.2 SUBMITTALS

- A. Manufacturer Certificate of Compliance for materials.
- B. Product Data: Manufacturer's data sheet on each type of product furnished.

## **PART 2: MANUFACTURER**

### 2.1 MANUFACTURER

Acceptable Manufacturer:  
Heckmann Building Products  
110 Richards Ave.  
Norwalk, CT 06854-1685  
800-621-4140  
Email: [info@heckmannanchors.com](mailto:info@heckmannanchors.com)  
Website: [www.heckmannanchors.com](http://www.heckmannanchors.com)

### 2.2 APPLICATIONS

- A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-16.
- B. ASTM A 36/A36M-14 Standard Specification for Carbon Structural Steel.

C. ASTM A1008/A1008M Sheet Metal Anchors and Ties (Plain Steel)

D. Stainless Steel AISI [Type 304] [or] [Type 316]

E. ASTM A240/A240M-15b Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Application.

F. ASTM A666-15 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.

G. Zinc Alloy 710 for use as a firewall anchor.

## 2.3 MATERIALS

### A. Products

#### **#340 Corrugated L-Anchor**

[gage] x [width] x [length (od)] x [bend length (od)]

#### **#340-A Corrugated L-Anchor with Hole**

[gage] x [width] x [length (od)] x [bend length (od)] x [centered hole diameter]

#### **#340-B Corrugated L-Anchor with Slot**

[gage] x [width] x [length (od)] x [bend length (od)] x [centered hole diameter]

#### **341 L-Anchor with Hole**

[gage] x [width] x [length (od)] x [bend length (od)] x [centered hole diameter]

#### **#341-A L-Anchor with Two Holes**

[gage] x [width] x [length (od)] x [bend length (od)] x [centered bend hole diameter]  
x [length hole diameter] [length hole distance from end]

#### **#341-B L-Anchor with Hole and Slot**

[gage] x [width] x [length (od)] x [bend length (od)] x [centered hole diameter] x  
[slot opening and length] x [center of slot from end]

#### **#342 L-Anchor with Slot**

[gage] x [width] x [length (od)] x [bend length (od)] x [centered slot opening and  
length]

#### **#342-A L-Anchor with Hole and Slot**

[gage] x [width] x [length (od)] x [bend length (od)] x [centered slot opening and  
length] x [slot opening and length] x [center of slot from end]

#### **#342-B L-Anchor with Two Slots**

[gage] x [width] x [length (od)] x [bend length (od)] x [centered slot opening and  
length] x [slot opening and length] x [center of slot from end]

B. Materials: [Plain Steel] [Stainless Steel Type 304] [Stainless Steel Type 316]  
[Zinc Alloy 710 Firewall]

## PART 3: EXECUTION

A. Install as specified in applicable masonry section(s).