

#371 Continuous Wire

SECTION 04 00 00 MASONRY  
Section 04 05 19.16 Masonry Anchors

**PART 1: GENERAL**

1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

**PART 2: MANUFACTURER**

2.1 MANUFACTURER

Acceptable Manufacturer:  
Heckmann Building Products  
110 Richards Ave.  
Norwalk, CT 06854-1685  
800-621-4140  
Email: [info@heckmannanchors.com](mailto:info@heckmannanchors.com)  
Website: [www.heckmannanchors.com](http://www.heckmannanchors.com)

2.2 APPLICATIONS

A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-16.

B. ASTM A 36/A36M-14 Standard Specification for Carbon Structural Steel.

C. ASTM A1008/A1008M Sheet Metal Anchors and Ties (Plain Steel)

D. ASTM A153/A153M-16 Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware

E. Stainless Steel AISI [Type 304] [or] [Type 316]

F. ASTM A580/A580M-15 Standard Specification for Stainless Steel Wire

## 2.3 MATERIALS

### **NO. 371 CONTINUOUS WIRE**

[9 gage] [3/16" diameter] wire in 10 ft. lengths.

Materials: [Hotdip Galvanized After Fabrication] [Type 304 Stainless Steel]

### **PART 3: EXECUTION**

- A. Install as specified in applicable masonry section(s).
- B. Hook continuous wire onto Heckmann #363 Plastic Seismic Clip attached to the masonry veneer anchor.