

Submittal Sheet
#442 Horseshoe Shim Washers

Used for shimming anchors or Shelf Angles against concrete walls that are uneven.
 Manufactured from a fire retardant engineered multipolymer plastic formulated for use as a bearing material. The compressive strength is between 10,000 and 12,000 psi.



Standards:

	Standard No.	Shim Size	Bolt Size
<input type="checkbox"/>	442-14	1/4" x 1-1/2" x 2"	1/2"
<input type="checkbox"/>	442-16	1/16" x 1-1/2" x 2"	1/2"
<input type="checkbox"/>	442-18	1/8" x 1 1/2" x 2"	1/2"
<input type="checkbox"/>	442-24	1/4" x 2-5/16" x 3"	3/4"
<input type="checkbox"/>	442-26	1/16" x 2-5/16" x 3"	3/4"
<input type="checkbox"/>	442-28	1/8" x 2-5/16" x 3"	3/4"
<input type="checkbox"/>	442-34	1/4" x 1-1/2" x 3-1/2"	1/2"
<input type="checkbox"/>	442-36	1/16" x 1-1/2" x 3-1/2"	1/2"
<input type="checkbox"/>	442-38	1/8" x 1-1/2" x 3-1/2"	1/2"

Quantity: _____