

#585 Joist Bent Anchor
#586 Twisted Joist Bent Anchor

SECTION 04 00 00 MASONRY
Section 04 05 19.16 Masonry Anchors

PART 1: GENERAL

1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

PART 2: MANUFACTURER

2.1 MANUFACTURER

Acceptable Manufacturer:
Heckmann Building Products
110 Richards Ave.
Norwalk, CT 06854-1685
800-621-4140
Email: info@heckmannanchors.com
Website: www.heckmannanchors.com

2.2 APPLICATIONS

A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-22.

B. ASTM A653/A653M-11 Standard Specification for Steel Sheet, Zinc-Coated (Mill Galvanized)

2.3 MATERIALS

A. NO. 585 JOIST BENT ANCHOR

1/8" x 1" wide x 17" long with three 7/32" nailing holes centered 1", 4" and 7" from the end + a 2" od bend. 12 Gauge mill galvanized.

B. NO. 586 TWISTED JOIST BENT ANCHOR

1/8" x 1" wide x 17" long with three 7/32" nailing holes centered 1", 4" and 7" from the end + a 2" od bend. 12 Gauge Mill Galvanized. Twist to start 11-1/2" from the end with the nailing side.

Materials: [Mill Galvanized]

PART 3: EXECUTION

A. Install as specified in applicable masonry section(s).