

## #84 WEEP-THRU MORTAR DEFLECTOR

### SECTION 042000 UNIT MASONRY Section 04 05 23 Masonry Accessories

#### **PART 1: GENERAL**

##### 1.1 RELATED SECTIONS

A. Section 07 25 00 - WeatherBarriers

##### 1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

#### **PART 2: MANUFACTURER**

##### 2.1 MANUFACTURER

Heckmann Building Products  
110 Richards Ave.  
Norwalk, CT 06854-1685  
800-621-4140  
Email: [info@heckmannanchors.com](mailto:info@heckmannanchors.com)  
Website: [www.heckmannanchors.com](http://www.heckmannanchors.com)

##### 2.2 APPLICATIONS

A. Provide systems that comply with the Building Code Requirements for Masonry Structures TMS 402-22.

##### 2.3 MATERIALS

Open mesh to collect and prevent mortar droppings from clogging weep vents.  
*Select Size:* [#84-5 - 1/2" thick] [#84-1 1" thick] [#84-2 – 2" thick]

#### **PART 3: EXECUTION**

- A. Install as specified in applicable masonry section(s).
- a. Extend flashing at least 6" above the top of the Weep-Thru Mortar Deflector.

- b. Remove all mortar droppings at the bottom of the cavity before installing the Weep-Thru Mortar Deflector.
- c. Install a continuous row of the Weep-Thru Mortar Deflector in the cavity at the base directly on the flashing with the dovetail facing upward.

END OF SECTION