

MATERIAL SPECIFICATIONS

Stainless Steel:

Sheet metal anchors and ties: ASTM A 666, ASTM

A 240/A240M AISI Type 304.

Wire: ASTM A580 AISI Type 304

(AISI Type 316 available upon request)

Hot-dip Galvanized:

ASTM A 153 Class B-2: (1.50 oz/ ft2.)(0.46kg/m2)

Mill Galvanized

Sheet metal anchors and ties: ASTM A641/A641M (0.10 oz sq ft) (11 ga and lighter only)

Plain Carbon Steel:

Sheet metal ASTM A1008/ A1008M Structural Steel ASTM A36/A36M-08

Wire: ASTM A 1064/A1064M - ASTM

Firewall Anchors:

Rolled Strip Zinc Alloy 710. (Firewall alloy 1/8" only)

All the above are compliant with the TMS 402 Building Code Requirements for Masonry Structures

Phone: (800) 621-4140

Heckmann is not responsible for your choice of anchors and dimensions for your project. The choice of anchors and products should be decided by the architects or engineers knowledgeable with the project. Once a custom order has been placed it cannot be canceled or returned. Any changes to the original order may require additional charges. Your signature is required for us to proceed. By signing any order, you agree that you have reviewed the details and specifications of the custom order and that said details and specifications are per your request. Further, by signing this order you are waiving any claim against or right of non-payment for products produced to the specifications of the order.