

**Rubble Stone Anchors**  
#398-C L-Type Rubble Clips  
#398-J J-Hook Rod  
#398 Rubble Stone Wire Tie

SECTION 04 00 00 MASONRY  
Section 04 05 19.16 Masonry Anchors  
Section 04 05 19.29 Stone Anchors

**PART 1: GENERAL**

1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

**PART 2: MANUFACTURER**

2.1 MANUFACTURER

Acceptable Manufacturer:  
Heckmann Building Products  
110 Richards Ave.  
Norwalk, CT 06854-1685  
800-621-4140  
Email: [info@heckmannanchors.com](mailto:info@heckmannanchors.com)  
Website: [www.heckmannanchors.com](http://www.heckmannanchors.com)

2.2 APPLICATIONS

A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-22.

E. Stainless Steel AISI [Type 304]

F. ASTM A240/A240M-15b Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Application.

G. ASTM A666-15 Standard Specification for Annealed or Cold-Worked

Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.

H. ASTM A580/A580M-15 Standard Specification for Stainless Steel Wire

## 2.3 MATERIALS

### A. Products

#### **#398-C L-Type Rubble Clips**

12 gauge x 2-3/4" wide x [length (od)] x [bend length (od)] x [centered hole diameter] x horizontal 13/32" x 1-1/4" slot centered [inches] from end.

#### **#398-J J-Hook Rod**

[[5/16" diameter] [3/8" diameter] x 52" long

#### **#398 Rubble Stone Wire Tie**

[3/16" diameter] x length [3"] [4"] [5"] [6"] [7"] [9"] with welded 3/16" dia crossbar

B. Materials: [Type 304 Stainless Steel]

## **PART 3: EXECUTION**

A. Install as specified in applicable masonry section(s).